



Face of goal shall be constructed of 4" square extruded 6063-T6 aluminum with minimum 3/4" corner radii for safety and a minimum wall thickness of 2/25". Extrusions shall have a net track extruded in the rear face to allow net attachment using specially designed clips included with each system. Goal shall have a 21' wide x 7' high opening. The backstays and rear stabilizer bar shall be constructed of 1 5/8" diameter x 13 ga. minimum galvanized steel tube and provide a 4' top depth x 7' bottom depth. 4" square face of the goal shall have a white textured polyester powder coated finish. Goal shall carry an 8-year limited warranty and comply with ASTM F2056. Each goal shall include two 11" diameter by 12" wide molded polyethylene ballast drums that act as rear ballast to comply with ASTM F2056 when filled with sand at time of installation. Rear drums shall rotate on a tubular rear horizontal stabilizer bar and serve as transport wheels. Additional standard features shall include molded plastic net attachment clips, 4mm white nets, Velcro net straps and net ground stakes. Installation to be completed in accordance to manufacturer's instructions. Do not scale drawings. System shall weigh approximately 490#/pair.



PRODUCT SPECIFICATION

SC2170PA44NT 4" SQUARE SHOOTOUT™ NO-TIP™ PORTABLE ALUMINUM SOCCER GOALS

REVISED 7/1/17