



Specifications & Options On Page 2



PRODUCT SPECIFICATION

WP2USFW SOLID COLOR FLANGE MOUNT WALL PADDING

REVISED 2/8/2018

Flat Wall Padding Options

| Model Number | Style | Foam | Backing | Vinyl Cover | Mounting System |
|--------------|------------|-----------------|-----------|--------------------|-----------------|
| WP2USFW | Protector™ | 2" Polyurethane | 7/16" OSB | 14 oz. Solid Color | Flange |
| WP2USZW | Protector™ | 2" Polyurethane | 7/16" OSB | 14 oz. Solid Color | Z-Track |
| WP2USVW | Protector™ | 2" Polyurethane | 7/16" OSB | 14 oz. Solid Color | Velcro |
| WP2USVS | Protector™ | 2" Polyurethane | Soft Back | 14 oz. Solid Color | Velcro |
| WP2UGFW | Protector™ | 2" Polyurethane | 7/16" OSB | 14 oz. Graphic | Flange |
| WP2UGZW | Protector™ | 2" Polyurethane | 7/16" OSB | 14 oz. Graphic | Z-Track |
| WP2UGVW | Protector™ | 2" Polyurethane | 7/16" OSB | 14 oz. Graphic | Velcro |
| WP2UGVS | Protector™ | 2" Polyurethane | Soft Back | 14 oz. Graphic | Velcro |
| WP2NSFW | Firewall | 2" Neoprene | 7/16" OSB | 14 oz. Solid Color | Flange |
| WP2NSZW | Firewall | 2" Neoprene | 7/16" OSB | 14 oz. Solid Color | Z-Track |
| WP2NSVW | Firewall | 2" Neoprene | 7/16" OSB | 14 oz. Solid Color | Velcro |
| WP2NSVS | Firewall | 2" Neoprene | Soft Back | 14 oz. Solid Color | Velcro |
| WP2NGFW | Firewall | 2" Neoprene | 7/16" OSB | 14 oz. Graphic | Flange |
| WP2NGZW | Firewall | 2" Neoprene | 7/16" OSB | 14 oz. Graphic | Z-Track |
| WP2NGVW | Firewall | 2" Neoprene | 7/16" OSB | 14 oz. Graphic | Velcro |
| WP2NGVS | Firewall | 2" Neoprene | Soft Back | 14 oz. Graphic | Velcro |

Padding Upgrade Options

WPUP3U

Upgrade any 2" polyurethane foam wall padding to 3" polyurethane foam for added player protection or to meet local codes or project specifications.

WPUP3N

Upgrade any 2" neoprene foam wall padding to 3" neoprene foam for added player protection or to meet local codes or project specifications.

WPUP2HD

Upgrade any 2" polyurethane foam wall padding to 2" high density foam for added player protection or to meet local codes or project specifications.

WPUPFRC

Upgrade any wood backed wall padding to add a fire retardant coating to the 7/16" OSB backing to meet local codes or project specifications.

WPUPVONAR

Upgrade to add Vonar fire retardant fabric to any wood backed wall padding to meet local codes or project specifications.

COLOR SELECTION

Select desired pad color from:

(<https://www.bisoninc.com/color-options/>)

Specify Color: _____

Protector™ Wall Padding Specifications (Standard Specs)

All full color graphic and solid color Protector wall padding including custom corner, column, door and stage padding is constructed of polyurethane foam with an Indentation Load Deflection (ILD) of 43-53 lbs. per 50 cubic inches and 1.50 pounds per cubic foot density per ASTM Tests B1 and A Foam conforms to California Fire Code TIB 117:2013 Section 3 and FMVSS 302 Foam also conforms to ISO 20743:2007 Antibacterial and AATCC 30 Antifungal Standards 14 ounce vinyl covering has a ASTM D2261 tear strength of 92 x 83 pounds per inch and has been treated for mildew and UV protection Vinyl conforms to NFPA-701 CSFM and Class A ASTM E-84 Wood backed padding is mounted on 7/16" OSB composite board with the foam attached to the OSB with water based adhesive.

Firewall™ Wall Padding Specifications (Standard Specs)

Full color graphic and solid color firewall padding including custom corner, column, door and stage padding is constructed of neoprene foam with Indentation Load Deflection (ILD) of 90-110 per ASTM D3574 Test B1 and a density of 1.90 - 2.10 pound per cubic foot per ASTM D3574 Test A Firewall neoprene foam passes California Fire Code TIB 117:2013 14 ounce vinyl covering has a ASTM D2261 tear strength of 92 x 83 pounds per inch and has been treated for mildew and UV protection Vinyl conforms to NFPA-701 CSFM and Class A ASTM E-84 Wood backed padding is mounted on 7/16" OSB composite board with the foam attached to the OSB with water based adhesive Assembled padding has been tested and meets NFPA 286.

REVISED 2/8/2018